SOLAR GARDEN LIGHT DATASHEET

Model: BST-GGD-005

Key Features

- Durable & Weatherproof: Aluminium housing with IP65 rating for outdoor use.
- Long Battery Life: LiFePO4 battery with over 2000 charge cycles and more than 10 years' lifespan.
- High Efficiency: Monocrystalline solar panel for optimal energy conversion.
- Smart Operation: Automatic dusk-to-dawn lighting.
- Bright & Adjustable: High-lumen SMD3030 LEDs with wide color temperature range (3000–6500K).
- Low Maintenance: Self-sustaining system requiring minimal upkeep.

Parameter Specification
Model BST-GGD-005

Solar Panel Power 5V 30W

Solar Panel Type Monocrystalline **LED Chips** 120 pcs SMD3030

Color Temperature 3000–6500K

Battery Type LiFePO4

Battery Capacity 3.2V 36,000 mAh

Charge Time 4–6 Hours

Working Mode Automatically ON at night, OFF at day

Housing Material Aluminum housing

Unit Size (mm) $\emptyset 480 \times H410$

IP Rating IP65

Lighting Duration Depends on usage and sunlight conditions

Warranty 2 years (lamp), 10 years (battery life expectancy)

Applications

- Garden and landscape lighting
- Pathway and driveway illumination
- Residential and commercial outdoor spaces
- Parks, resorts, and recreational areas

Contact Information

• **Brand:** Entelechy

• **Email:** bultecenginneringsolutions@gmail.com

• Website: www.entelechy-ug.com

• **Phone:** +256 200 930 008

• Address: Plot 58 Ntinda – Kisasi Road